

COLORSTEP® 0 VIOLET X4003

颜料索引: Pigment Violet 3

C.I.No: 42535

化学名称: 青莲色淀

CAS No. 1325-82-2

理化数据

筛余 (120mesh)	≤5.0
吸油量(ml/100g)	40-50
PH 值 (at g/l .C)	6-7
水溶物 (@ 20°C)	≤1.5
水份(%)	≤1.5

牢度性能

耐迁移	4
耐光 - (全色)	6
耐光 - SD 1/3 (Reduction)	6
耐温 - (全色)[°C]	160
耐温 - SD 1/3 (Reduction) [°C]	160

产品描述

是蓝光紫色粉末，比颜料紫 1 和颜料紫 2 均要明显偏蓝光，耐光牢度比颜料紫 27 要优良，主要用于油墨，如包装油墨，水性柔版油墨等，而且多制成挤水转相色膏，色片剂型，应用在胶版印刷油墨，亦可用于文教用品着色。

应用领域

一般工业漆	不推荐
卷材涂料	不推荐
粉末涂料	不推荐
PO	不推荐
PVC & 橡胶	不推荐
工程塑料	不推荐
油墨	推荐

化学性能

耐酸	5
耐碱	5
耐乙醇	4
耐酯	4
耐苯	4
耐酮	4
耐皂洗	4

化学品名录状况

COLORSTEP® 0 VIOLET X4003 所有成分 在下列国家化学品名录中列明

AICS (澳大利亚)、DSL (加拿大)、ECL (韩国)、EINECS [欧洲]、IECSC [中国]、MITI [日本]、NZIOC (新西兰)、PICCS (菲律宾)

TSCA [美国]

NOTICE: All statements, information, and data given herein are believed to be accurate and reliable but are presented without guaranty, warranty, or responsibility of any kind, express or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement, and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated, or that other measures may not be required.