

## **COLORSTEP®O Yellow 1068**

颜料索引: Pigment Yellow 168

**C.I.No**: 13960 **CAS No**. 71832-85-4

理化数据	
筛余 (120mesh)	≤5.0
吸油量(ml/100g)	35-45
PH 值 (at g/I .C)	5-6
水溶物 (@ 20℃)	≤1.0
水份(%)	≤1.5

牢度性能	
耐迁移	5
耐光 - (全色)	7
耐光 - SD 1/3 (Reduction)	7
耐温 - (全色)[℃]	270
耐温 - SD 1/3 (Reduction) [°C]	270

单偶氮色淀

## 产品描述

该品种为稍绿光黄色调,对脂肪烃与芳香烃有优良耐溶剂及耐迁移性,主要用于涂料与塑料的着色,在塑料 PVC 中有良好耐迁移性能,色力稍低,耐光牢度为 7 级,主要推荐用于 LDPE 的着色。

化学名称:

应用领域		
一般工业漆	推荐	
卷材涂料	推荐	
粉末涂料	推荐	
РО	推荐	
PVC &橡胶	推荐	
工程塑料	推荐	
油墨	推荐	

化学性能	
耐酸	5
耐碱	5
耐乙醇	5
耐酯	5
耐苯	5
耐酮	5
耐皂洗	5

## 化学品名录状况

COLORSTEP®O Yellow 1068所有成分 在下列国家化学品名录中列明

AICS (澳大利 亚)、DSL (加拿大)、ECL (韩国 )、EINECS [欧洲], IECSC [中国]、 MITI [日本]、NZIOC (新西兰)、PICCS(菲利宾)
TSCA [美国]

**NOTICE:** All statements, information, and data given herein are believed to be accurate and reliable but are presented without guaranty, warranty, or responsibility of any kind, express or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement, and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated, or that other measures may not be required.